

**Motor Mower Aebi AM9:  
the technical data.**

<b>Engine</b>	ACME ACT 280 OHC, gasoline, four-stroke, 275 cm <sup>3</sup> , air cooled, 7 kW (9.5 HP). Dry-air filter, regulator, ignition coil 12V-25W, rotating fan-screen, reversing starter with automatic compression release, cut-off switch on the steering bar.	<b>Tyres</b>	Studded tyres, 4.00-8/2PR
<b>Clutch</b>	Multi-plate dry clutch, clutch brake.	<b>Tyre options / attachments</b>	Large tyres, 16x6.50-8, cage-wheels and double cage-wheels with quick-action connectors, double-tyres, snow chains.
<b>Brakes</b>	Running and parking brakes.	<b>Track width</b>	420 mm
<b>Transmission</b>	Sput-wheel gearbox with pinion drive to the drive axle, running in an oil-bath. <i>Forward:</i> 2 forward speeds (3.0 and 4.8 km/h) <i>Reverse:</i> 1 reverse speed (3.7 km/h) Mowing attachment	<b>Weight</b>	Approx. 170 kg, depending on equipment fitted.
<b>PTO</b>	829 rpm.	<b>Attachments</b>	Normal or medium cutter bar, 1.45 - 1.90 m, universal bar, 1.17 - 1.68 m, communal bar, 1.17 and 1.48 m, band hay rake Aebi 2.10 m, snow-plough 1.40 m, suction sweeper, 0.85 m.
<b>Quick-action Attachment Connection</b>	Coupling-hub with involute toothing	<b>Additional equipment</b>	Special silencer, push-on connector for standard container.  With reservation to any technical modifications.
<b>Steering</b>	Rubber-covered grips with height adjustment, "dead mans"-handle.		

---

**Aebi & Co. AG  
Farm and Public  
Works Equipment  
CH-3401 Burgdorf**

**Phone +41 (0)34 421 61 21  
Fax +41 (0)34 421 61 51  
www.aebi.com  
aebi@aebi.com**

**AEBI**