

TRR HYDRAULIC PRUNING SHREDDERS 40 to 120 C.V.

10 mm shell and lateral sections with structural reinforcements.

High performance professional model

With 10mm replaceable blades or hammers.

Comes with crumbling saws and counter-saws.

Casting rotor-bearing supports.

480 mm rotor diameter. 220 mm rear bearing diameter.

Double row auto-oscillating barrel bearings.

Includes normal drive, bolts and pins.

Shredding capacity up to 12cm to 14cm diameter and grass.

With hydraulic lateral displacement



MODEL	N° OF BLADES / HAMMERS	CUT WIDTH	TOTAL WIDTH	MAX POWER	WEIGHT
TRR-125	24/12	1,250	1,410	40 - 120	585
TRR-150	32/16	1,500	1,660	60 - 120	673
TRR-175	40/20	1,750	1,910	65 - 120	761
TRR-200	48/24	2,000	2,160	80 - 120	849
TRR-230	56/28	2,300	2,460	90 - 120	955
TRR-250	56/28	2,500	2,660	100 - 120	1.030
TRR-280	64/32	2,800	2,960	100 - 120	1.125

OPTIONS:

CODE	DESCRIPTION
01108	CYLINDER REF. WITH HOSES AND VALVE
01120	CYLINDER REF. LONG WITH HOSES AND VALVE
01075	REAR HYDRAULIC WHEELS (NO ROLLER)
01074	REAR MECHANIC WHEELS (NO ROLLER)
01072	TRANSMISSION WITH FREE WHEEL
Z1238	THIRD POINT CHAIN
20086	REAR GRILLE
01191	CURTAIN WITH CHAINS