

FI MODEL 100 to 180 C.V.

Reverse rotation as tractor moves forward to bury stones.

Reinforced lateral gear drive.

Nodular casting crankcase and group.

Shaft speed 540 or 1000 r.p.m.

Fixed front skirt with rear grilles for stone sifting.

Includes reinforced drive with safety clutch.

6 blades per disc, bolts and pins.

Rear curved collector for higher definition.

Revolutions and characteristics adapted to each tractor.

Tractors with maximum shaft height of 70cm.

Reinforced oil-tight cutting edges, with axial joints.

Reinforced chassis and turret with optional hydraulic ridgers or rollers.



MODEL	N° OF BLADES	CUT WIDTH	TOTAL WIDTH	MAX POWER	WEIGHT
FI-39	39	1,786	1,914	80 - 180	980
FI-42	42	1,910	2,038	90 - 180	1.000
FI-45	45	2,049	2,177	100 - 180	1.020
FI-48	48	2,173	2,301	110 - 180	1.040
FI-51	51	2,312	2,440	115 - 180	1.060
FI-54	54	2,436	2,564	120 - 180	1.080
FI-57	57	2,575	2,703	130 - 180	1.100
FI-60	60	2,699	2,827	140 - 180	1.120

OPTIONS:

CODE	DESCRIPTION
01020	FOLDABLE MECHANICAL FLAPS
01062	FOLDABLE HYDRAULIC FLAPS
01000	SPLINED TRANSMISSION
01186	TRANSMISSION WITH TORQUE LIMITER
01005	10mm BLADE AND SPECIAL SCREW
01097	TOP DISCS
01039	RIGHT SIDE GRILLE