## TM FED SHREDDER (REAR) WOOD 75 to 160 C.V.

Total working # width of just 17.5cm Singular transmission only lateral

8 mm shell and lateral sections with 8mm structural reinforcements.

Includes free wheel drive, bolts and pins.

Reversible hydraulic feeding pump.

Self-fed for rocky or tilled land.

480 mm rotor diameter.

2 automatic tensioners, in feeder and rotor.

Twin reinforced feeder chain.

Flow controller (as standard)

220 mm rear roller vibration reducer.

Double row auto-oscillating barrel bearings.

With roller feeder. For all types of tractors.

Shredding capacity up to 16cm in diameter.

Casting rotor-bearing supports.

Special wood shredder, with high capacity shredding.

Comes with hammers, crumbling saws and counter-saws.



MODEL	N° OF BLADES / HAMMERS	CUT WIDTH	TOTAL WIDTH	MAX POWER	WEIGHT
TM-150	32/16	1,500	1,675	75 - 160	990
TM-175	40/20	1,750	1,925	85 - 160	1.140
TM-200	48/24	2,000	2,175	95 - 160	1.300

## **OPTIONS:**

CODE	DESCRIPTION
01108	CYLINDER REF. WITH HOSES AND VALVE
01120	CYLINDER REF. LONG WITH HOSES AND VALVE
01074	REAR MECHANIC WHEELS (NO ROLLER)