

FS MODEL 80 to 180 C.V.

Reinforced chassis and turret with optional hydraulic ridgers or rollers.

Reinforced oil-tight cutting edges, with axial joints.

Revolutions and characteristics adapted to each tractor.

Centred with Nodular casting crankcase and group.

Includes reinforced drive with safety clutch.

Rear curved collector for higher definition.

6 blades per disc, bolts and pins.

Reinforced lateral gear drive.

Tractors with maximum shaft height of 85cm.

With 1 speed high group for raised shaft.



MODEL	N° OF BLADES	CUT WIDTH	TOTAL WIDTH	MAX POWER	WEIGHT
FS-45	45	2,049	2,177	80 - 180	975
FS-48	48	2,173	2,301	90 - 180	995
FS-51	51	2,312	2,440	100 - 180	1.015
FS-54	54	2,436	2,564	110 - 180	1.035
FS-57	57	2,575	2,703	115 - 180	1.055
FS-60	60	2,699	2,827	120 - 180	1.075
FS-63	63	2,838	2,963	125 - 180	1.105
FS-66	66	2,962	3,092	130 - 180	1.120

OPTIONS:

CODE	DESCRIPTION
01020	FOLDABLE MECHANICAL FLAPS
01062	FOLDABLE HYDRAULIC FLAPS
01000	SPLINED TRANSMISSION
01186	TRANSMISSION WITH TORQUE LIMITER
01010	SPLIT HORIZONTAL COLLECTOR
Z1323	FLAP COVERS AND STAINLESS STEEL COLLECTOR
01005	10mm BLADE AND SPECIAL SCREW
01097	TOP DISCS
01039	RIGHT SIDE GRILLE
01164	STRAIGHT BLADE (4 PER SQUARED DISC)
4/DISCO	4 BLADES/DISC FOR "FANGUEO" (RICE)