

MODELO F2 de 100 a 180 C.V.

- Twin shafts for optimal two way forward movement.**
- Reinforced lateral gear drive.**
- Nodular casting crankcase and group.**
- 2 shafts required of 540 and 1,000 r.p.m.**
- Includes reinforced drive with safety clutch.**
- To work on either dry or wet land.**
- 6 twin edged blades per special disc (patented).**
- Rear curved collector for higher definition.**
- Revolutions and characteristics adapted to each tractor.**
- Reinforced oil-tight cutting edges, with axial joints.**
- Reinforced chassis and turret with optional hydraulic ridgers or rollers.**
- Front skirt and rear removable grilles to switch forward moving direction.**
- Twin direction rotation gearbox for stone burial and basic tiller.**



MODEL	N° OF BLADES	CUT WIDTH	TOTAL WIDTH	MAX POWER	WEIGHT
F2-39	39	1,786	1,914	80 - 180	1.055
F2-42	42	1,910	2,038	90 - 180	1.075
F2-45	45	2,049	2,177	100 - 180	1.095
F2-48	48	2,173	2,301	110 - 180	1.115
F2-51	51	2,312	2,440	115 - 180	1.135
F2-54	54	2,436	2,564	120 - 180	1.155
F2-57	57	2,575	2,703	130 - 180	1.175
F2-60	60	2,699	2,827	140 - 180	1.195
F2-63	63	2,838	2,963	150 - 180	1.225
F2-66	66	2,962	3,092	160 - 180	1.240

OPTIONS:

CODE	DESCRIPTION
01020	FOLDABLE MECHANICAL FLAPS
01062	FOLDABLE HYDRAULIC FLAPS
01000	SPLINED TRANSMISSION
01186	TRANSMISSION WITH TORQUE LIMITER
01005	10mm BLADE AND SPECIAL SCREW
01097	TOP DISCS
01039	RIGHT SIDE GRILLE