















Even finish on uneven ground

Two fully independent rear-discharge wheeled rotary decks adjust to all angles when mowing banks, ditches, and hillocks. With hydraulic drive they mow in any position.

Superior by design

Concentric cutting unit design creates an overlap so that no central band of grass is left uncut. Cutting height is variable, and the swing-tip blades can be fixed for use on shorter grass. For maintenance, manual override allows tilting of the central "bike" and decks can be raised giving access to the blades from either side of

Superb performance

The mower to bank on

Powered by a 30hp Yanmar water-cooled 3-cylinvoir banks and other uneven terrains.

Operator comfort and safety

Heavy duty welded steel

25" 12,5"-12": pressure from 0,7 to 1,1 har

16.5"*6,5"*-8" (full wheels)

ydraulic; Parking with drum on back wheel

1080 Kg

Two independent steel decks

Parallel linkage

symmetrical 91,5 cm blades - overlapping 3 cm

Contra-rotating

Hydraulic

Blades with swing tips

From 50 to 152 mm

Operator presence microswitch (seat)

Mechanical Hydraulic thermal trip

Slope sound signalling right/left maximum

A slope alarm sounds on banks above 27 degrees and an operator presence switch is fitted. A comfortable seat, low noise, ease-of-operation and good visibility minimise operator fatique.

Technical specifications



Piston displacement Maximum power Alternator Battery Fuel Tank capacity

Operating time Oil Capacity TRANSMISSION

Hydraulic Forward speed Reverse speed Differential lock

Oil tank TRACTOR

Chassis Central wheel

Brake

Weight

Side wheels

CUTTING SYSTEM

Number of blades

rotation direction

Blades protection against impact

Blade clutch

Cutting width

Cutting height

Parking brake


NOISE LEVEL

Cutting deck Installation





2692 1890	
A 180	WATERCOOLED 30HP DIESEL ENGINE
YAMILAR Diesel 3T NE 82A	
3 cylinder / water-cooled	
1331 cm ²	
30hp at 3000 rpm	
12V/40A	
12Y/45A	
Diesel	
52 litres	
8 hours in normal conditions	
3,8 litres Oil [with cartridge]	
	THE REPORT OF THE PERSON OF TH
hydraulic engine	
From 0 to 13 kph	
From 0 to 11 kph	BANK MOVING
Hydraulic, permanent	BANK MOWING
30 litres	



OPERATOR COMFORT AND SAFETY

PERFECT FOR GULLEYS



der diesel engine, attila A180 has hydrostatic drive, power steering and hydraulic drive to the cutting units. It is specially designed for large sites :- motorway banks ; industrial estates ; reser-

