

Robust

Chassis

Etesia's ATTILA 85 has a strengthened welded tubular chassis. The side-discharge steel deck plus blade protection system ensure

Powerful

Hydrostatic transmission

Hydrostatic transmission gives variable speed to enable the operator to adjust to the prevailing conditions. An easy to engage differential lock provides extra traction in difficult terrain.

Low centre of gravity, plus long wheel base and agricultural tyres give added stabillty and traction. ATTILA 85 can be used on slopes up to 30 degrees.

The 85 cm cutting width plus swing or fixed-tip blades produces high productivity.

Comfortable

Central cutting height adjustment plus rack and pinion steering make the ATTILA 85 brushcutter easy to operate.

Technical specifications







	AK 85
Engine	KAWASAKI 14 PS – 423 cm ³
Weight	250 kg
Cutting width	85 cm
Cutting height	50-60-75-90 cm by central lever
Blade	7 mm thick with 2 swing tip blades
Mower deck	2 mm steel
Blade clutch	Mechanical
Ejection	Side-discharge
Chassis	Tubular welded frame
Forward	Hydrostatic
Forward speed	V:0-8 km/h-R:0-4 km/h
Parking brake	Mechanical
Tyres with agrarian profile	F: 7 x 35 – R: 16 x 7.8
Blades	MC 85 : blade for ATTILA 85





and brushwood.

